# Operating Systems UNIT -3 Paging

1

# **Overview**

- Paging
- Page Tables
- TLB
- Shared Pages
- Hierarchical Pages
- Hashed Pages
- Inverted Pages
- Uses

### **Address Translation Scheme**

Address generated by CPU is divided into:

- Page number (p) used as an index into a page table which contains base address of each page in physical memory
- Page offset (d) combined with base address to define the physical memory address that is sent to the memory unit

page number	page offset
р	d
m -n	n

• For given logical address space 2<sup>m</sup> and page size 2<sup>n</sup>

# Paging Hardware



#### Paging Model of Logical and Physical Memory



# Paging Example



# Paging (Cont.)

- Calculating internal fragmentation
  - Page size = 2,048 bytes
  - Process size = 72,766 bytes
  - 35 pages + 1,086 bytes
  - Internal fragmentation of 2,048 1,086 = 962 bytes
  - Worst case fragmentation = 1 frame 1 byte
  - On average fragmentation = 1 / 2 frame size
  - So small frame sizes desirable?
  - But each page table entry takes memory to track
  - Page sizes growing over time
    - Solaris supports two page sizes 8 KB and 4 MB
- Process view and physical memory now very different
- By implementation process can only access its own memory

### **Free Frames**



Before allocation

After allocation

### Implementation of Page Table

- Page table is kept in main memory
- Page-table base register (PTBR) points to the page table
- Page-table length register (PTLR) indicates size of the page table
- In this scheme every data/instruction access requires two memory accesses
  - One for the page table and one for the data / instruction
- The two memory access problem can be solved
  - by the use of a special fast-lookup hardware cache
  - called associative memory or translation look-aside buffers (TLBs)

# Implementation of Page Table

- Some TLBs store address-space identifiers (ASIDs) in each TLB entry –
  - uniquely identifies each process
  - provide address-space protection for that process
  - Otherwise need to flush at every context switch
- TLBs typically small (64 to 1,024 entries)
- On a TLB miss, value is loaded into the TLB for faster access next time
  - Replacement policies must be considered
  - Some entries can be wired down for permanent fast access

# **Associative Memory**

• Associative memory – parallel search

Page #	Frame #	

- Address translation (p, d)
  - If p is in associative register, get frame # out
  - Otherwise get frame # from page table in memory

### Paging Hardware With TLB



# **Effective Access Time**

- Associative Lookup
  - Extremely fast
- Hit ratio =  $\alpha$ 
  - Hit ratio percentage of times that a page number is found in the associative memory;
  - Consider  $\alpha$  = 80%, 100ns for memory access
- Consider  $\alpha$  = 80%, 100ns for memory access
  - EAT = 0.80 x 100 + 0.20 x 200 = 120ns
- Consider hit ratio α = 99, 100ns for memory access
  EAT = 0.99 x 100 + 0.01 x 200 = 101ns

# **Memory Protection**

- Memory protection implemented
  - by associating protection bit with each frame
  - to indicate if read-only or read-write access is allowed
  - Can also add more bits to indicate page execute-only, and so on
- Valid-invalid bit attached to each entry in the page table:
  - "valid" indicates that the associated page
    - is in the process' logical address space, and is thus a legal page
  - "invalid" indicates that the page I
    - is not in the process' logical address space
  - Or use page-table length register (PTLR)
  - Page Table Entries (PTEs) can contai more information
- Any violations result in a trap to the kernel

#### Valid (v) or Invalid (i) Bit In A Page Table



# **Shared Pages**

#### • Shared code

- One copy of read-only (reentrant) code shared among processes (i.e., text editors, compilers, window systems)
- Similar to multiple threads sharing the same process space
- Also useful for interprocess communication if sharing of read-write pages is allowed

#### • Private code and data

- Each process keeps a separate copy of the code and data
- The pages for the private code and data can appear anywhere in the logical address space

#### **Shared Pages Example**



# Structure of the Page Table

- Memory structures for paging can get huge using straightforward methods
  - Consider a 32-bit logical address space as on modern computers
  - Page size of 4 KB (2<sup>12</sup>)
  - Page table would have 1 million entries  $(2^{32}/2^{12})$
  - If each entry is 4 bytes -> 4 MB of physical address space / memory for page table alone
    - That amount of memory used to cost a lot
    - Don't want to allocate that contiguously in main memory
- Hierarchical Paging
- Hashed Page Tables
- Inverted Page Tables

### **Hierarchical Page Tables**

- Break up the logical address space into multiple page tables
- A simple technique is a two-level page table
- We then page the page table

#### **Two-Level Page-Table Scheme**



# Two-Level Paging Example

- A logical address (on 32-bit machine with 1K page size) is divided into:
  - a page number consisting of 22 bits
  - a page offset consisting of 10 bits
- Since the page table is paged, the page number is further divided into:
  - a 12-bit page number
  - a 10-bit page offset

•

• Thus, a logical address is as follows:

page number page offset

<i>p</i> <sub>1</sub>	<i>p</i> <sub>2</sub>	d	
12	10	10	

- where  $p_1$  is an index into the outer page table, and  $p_2$  is the displacement within the page of the inner page table
- Known as forward-mapped page table

### **Address-Translation Scheme**



### 64-bit Logical Address Space

- Even two-level paging scheme not sufficient
- If page size is 4 KB (2<sup>12</sup>)
  - Then page table has 2<sup>52</sup> entries
  - If two level scheme, inner page tables could be 2<sup>10</sup> 4-byte entries
  - Address would look like



- Outer page table has 2<sup>42</sup> entries or 2<sup>44</sup> bytes
- One solution is to add a 2<sup>nd</sup> outer page table
- But in the following example the 2<sup>nd</sup> outer page table is still 2<sup>34</sup> bytes in size
  - And possibly 4 memory access to get to one physical memory location

# **Three-level Paging Scheme**

outer page	inner page	offset
$p_1$	<i>p</i> <sub>2</sub>	d
42	10	12

2nd outer page	outer page	inner page	offset
$p_1$	$p_2$	<i>p</i> <sub>3</sub>	d
32	10	10	12

# Hashed Page Tables

- Common in address spaces > 32 bits
- The virtual page number is hashed into a page table
  - This page table contains a chain of elements hashing to the same location
- Each element contains
  - (1) the virtual page number
  - (2) the value of the mapped page frame
  - (3) a pointer to the next element
- Virtual page numbers are compared in this chain searching for a match
  - If a match is found, the corresponding physical frame is extracted
- Variation for 64-bit addresses is **clustered page tables** 
  - Similar to hashed but each entry refers to several pages (such as 16) rather than 1
  - Especially useful for sparse address spaces (where memory references are non-contiguous and scattered)

### Hashed Page Table



# **Inverted Page Table**

- Rather than each process having a page table and keeping track of all possible logical pages,
  - track all physical pages
- One entry for each real page of memory
- Entry consists of
  - the virtual address of the page stored in that real memory location,
  - information about the process that owns that page
- Decreases memory needed to store each page table
  - but increases time needed to search the table when a page reference occurs
- Use hash table to limit the search to one/few page-table entries
  - TLB can accelerate access
- But how to implement shared memory?
  - One mapping of a virtual address to the shared physical address

#### **Inverted Page Table Architecture**



# Functionality enhanced by page tables

- Code (instructions) is read-only
  - A bad pointer can't change the program code
- Dereferencing a null pointer is an error caught by hardware
  - Don't use the first page of the virtual address space mark it as invalid – so references to address 0 cause an interrupt
- Inter-process memory protection
  - My address XYZ is different that your address XYZ
- Shared libraries
  - All running C programs use libc
  - Have only one (partial) copy in physical memory, not one per process
  - All page table entries mapping libc point to the same set of physical frames
    - DLL's in Windows

# More functionality

- Generalizing the use of "shared memory"
  - Regions of two separate processes's address spaces map to the same physical frames
  - Faster inter-process communication
    - Just read/write from/to shared memory
    - Don't have to make a syscall
  - Will have separate Page Table Entries (PTEs) per process, so can give different processes different access rights
    - E.g., one reader, one writer
- Copy-on-write (CoW), e.g., on fork()
  - Instead of copying all pages, create shared mappings of parent pages in child address space
    - Make shared mappings read-only for both processes
    - When either process writes, fault occurs, OS "splits" the page

# Uses

- Memory-mapped files
  - instead of using open, read, write, close
    - "map" a file into a region of the virtual address space

- e.g., into region with base 'X'

- accessing virtual address 'X+N' refers to offset 'N' in file
- initially, all pages in mapped region marked as invalid
- OS reads a page from file whenever invalid page accessed
- OS writes a page to file when evicted from physical memory
  - only necessary if page is dirty

- Use "soft faults"
  - faults on pages that are actually in memory,
  - but whose PTE entries have artificially been marked as invalid
- That idea can be used whenever it would be useful to trap on a reference to some dataitem
- Example: debugger watchpoints
- Limited by the fact that the granularity of detection is the page